



INSULATION AS
REQUIRED

INTERIOR FINISH

FINISH FLOOR

WATERPROOF MEMBRANE

STUCCO LATH

STUCCO FINISH

STUCCO WEEP SCREED

Desert Brand CMFPS
COLOR FINISH

Desert Crete TEXTURE

2nd. Desert Crete BASE COAT

FIBERGLASS & Desert Brand
Bonder 480 MEMBRANE

GALV. METAL LATH &
Desert Crete BASE COAT

MIN. 4" x 4" 26 GA.
SHEET METAL BASE
FLASHING

5/8" MIN. PLYWOOD
SUBSTRATE SLOPE TO
DRAIN 1/4" PER FT. MIN.

ACTUAL FRAMING
NOT SHOWN FOR
CLARITY

1/2" CLEAR

2" MIN.

Desert Brand ©

RING SHANK ROOFING
NAILS @ 4" O.C.

GENERAL NOTES:
ISOLATE ALL COPPER & ALUMINUM MATERIALS FROM
FERROUS METALS BY APPLICATION OF Desert Crete
BOND COAT MATERIAL.

USE STAINLESS STEEL FASTENERS AT COPPER PANS
& FLASHINGS.

REFER TO ARCHITECTURAL & STRUCTURAL
DRAWINGS AND SPECIFICATIONS FOR ADDITIONAL
INFORMATION REGARDING PLYWOOD SHEATHING,
FRAMING, BLOCKING AND SHEET METAL
INSTALLATION.

Desert Crete Deck to Wall Detail

HILL BROTHERS CHEMICAL COMPANY

1675 N. Main St. Orange, CA 92867 (714) 998-8800 Fax: (714) 998-6310

Date: 10/10/05
Issue: Standards

SCALE: 1/2" = 1"

Desert Crete Detail
101